

Current BCS America Tractor Model Comparison Chart

Model	P/N <small>(R) Recoil Start (E) Electric Start</small>	Engine	Axle Type	Standard Wheels/ Tires	Standard Wheel Width	Working Speeds / Transport (Y/N)	Tiller Sizes	Brakes	Comments
620	8G4CS200 (R)	Honda GX240	Straight, Wheels Locked	4x10x18"	17.5"	3 Yes	N/A Front-Mount Only	No	Great for mowing, and snow clearing attachments. Front-Mount only.
710	821K0180 (R)	Kohler CH270	Straight, Wheels Locked	4x8x16"	16"	2 Yes	18" 20"	No	Smallest tractor w/ reversible handlebars, which are simplified compared to larger models. Great for tilling, limited attachment range.
718	821CR180 (R)	Honda GX200	Straight, Wheels Locked	4x8x16"	16"	2 Yes	18" 20"	No	A step up from the 710 with upgraded handlebars for increased operator comfort.
722	821CS280 (R) 821CT280 (E)	Honda GX240	Straight, Wheels Locked	4x10x18"	21"	2 Yes	20" 26"	No	Most popular straight axle model. Perfect for hobby gardeners and homesteaders with an expanded attachment range.
732	8C1K1280 (R) 8C1K2280 (E)	Kohler CH395	Differential Drive w/ Lockout	4x10x18"	21"	2 Yes	20" 26" 30"	No	Most economical of the Professional Series. Differential drive gives the operator a much wider range of compatible mowing attachments.
852	8H0CW780 (R) 8H0CX780 (E)	Honda GX390	Differential Drive w/ Lockout	5x12x22"	22"	3 Yes	26" 30"	Individual Wheel Brakes	Model 852 has only one difference from Model 853: The transport speed is accessible in Front-Mount mode instead of Rear.
853	8H0CW785 (R) 8H0CX785 (E)	Honda GX390	Differential Drive w/ Lockout	5x12x22"	22"	3 Yes	26" 30"	Individual Wheel Brakes	A third working speed and individual wheel brakes make the 853 perfect for multi-use, professional applications.
739 <i>PowerSafe</i>	8CCCU5A0 (R) 8CCCV5A0 (E)	Honda GX340	Differential Drive w/ Lockout	5x10x19"	22"	3 No	26" 30"	Parking Brake	A step up from the 732 with PowerSafe clutch technology, larger wheels, a Honda GX engine, and a third working speed for mowing and transport.
749 <i>PowerSafe</i>	8C8CW7A0 (R) 8C8CX7A0 (E)	Honda GX390	Differential Drive w/ Lockout	5x12x22"	22"	3 No	26" 30"	Individual Wheel Brakes, Parking Brake	The PowerSafe upgrade to model 853. Same attachment compatibility, but a better choice for frequent use of high-torque implements.
750 <i>PowerSafe</i>	8CBCW100 (R) 8CBCX100 (E)	Honda GX390	Differential Drive w/ Lockout	6.5x12x22"	26"	3 No	26" 30" 33"/33"HD	Individual Wheel Brakes, Parking Brake	Built for commercial tilling operations with gear-reduction mechanisms in the wheels to slow ground speed. With a reinforced PTO connection point, it's the only tractor built to handle the 33" HD Tiller.
770 <i>PowerSafe HYDRO</i>	8CFCW7A0 (R) 8CFCX7A0 (E)	Honda GX390	Hydrostatic Drive w/ Differential Lockout	5x12x22	27"	2 Ranges No	30" 33"	Individual Wheel Brakes, Parking Brake	The only tractor with Hydrostatic drive and reversible handlebars. Control ground speed and direction of travel with a single lever and without the need to shift or vary the throttle.
660 <i>PowerSafe HYDRO</i>	8H6AK000 (R)	Vanguard V-Twin	Hydrostatic Drive w/ Hydraulic Wheel Brakes	N/A Wheels Sold Separately	N/A Wheels Sold Separately	2 Ranges No	N/A Front-Mount Only	Hydraulic Wheel Brakes	Hydrostatic drive, hydraulic steering, and an engine rated for 30° slopes make this Front-Mount only machine perfect for professional groundskeepers and landscape contractors.